


MAF400 series

AIR UNIT (FILTER)



Symbol



Specification

Model	MAF400		
Bore No.	8A	10A	15A
Port size	1/4	3/8	1/2
Medium	Air		
Operating pressure range (*1.2)	0.05~1 MPa		
Proof pressure	1.5 MPa		
Ambient temperature	- 5~+60°C (No freezing)		
Filter element	Standard: 40μm, Option: 5μm		
Drain capacity	100 cm ³		
Max. flow rate(*3) ℓ /min(ANR)	1500	2000	2200
Weight	550 g		

*1. Standard unit contains semi-auto-drain function when operating pressure below 0.05 MPa.

*2. Choose auto-drain FMRF300, the pressure range is 0.15~1 MPa.

*3. Flow is at pressure P=0.7 MPa with pressure drop ΔP=0.03 MPa.

Order example

MAF400 – 8A – ND □ – □ – **B** – □

MODEL

PORT SIZE
8A: 1/4
10A: 3/8
15A: 1/2

BOWL
Blank: PC bowl
N: Nylon bowl

FLOW DIRECTION
Blank: Left to right
R: Right to left

FILTER ELEMENT
Blank: 40μm
5u: 5μm

Blank: Without
B: Bracket

PORT THREAD
Blank: Rc thread
G: G thread
NPT: NPT thread

Blank: Semi-auto drain
D: Auto drain valve (FMRF300)

